

App. No.: 10/840,172
Amendment

AMENDMENTS TO THE CLAIMS

1. (Currently amended): A method for use in free-space communications, comprising the steps of:

transmitting data in an active mode in an optical signal through a free-space optical path of a communication link extending across a terrestrial free-space region;

detecting degradation of the optical signal in the terrestrial free-space region; and

automatically switching from the active mode to a standby mode upon optical beam degradation in the terrestrial free-space region, wherein the standby mode includes transmitting data in a radio frequency (RF) signal through a free-space RF path of the communication link;

wherein an RF transceiver for generating the RF signal is active during the active mode and transmitting control and status information.

2. (Canceled).

3. (Original): A method in accordance with claim 1, wherein the step of detecting degradation of the optical signal in the terrestrial free-space region comprises the step of:

sensing a characteristic of a received optical signal.

4. (Original): A method in accordance with claim 3, wherein the characteristic of the received optical signal comprises a power level of the received optical signal.

5. (Original): A method in accordance with claim 3, wherein the characteristic of the received optical signal

App. No.: 10/840,172
Amendment

comprises a transmissive capability of the received optical signal.

6. (Original): A method in accordance with claim 3, further comprising the step of:

using the characteristic of the received optical signal to calculate a power adjustment for a station at an opposite end of the communication link.

7. (Original): A method in accordance with claim 1, wherein the degradation of the optical signal is due to atmospheric conditions in the terrestrial free-space region.

8. (Currently amended): An apparatus for use in free-space communications, comprising:

means for transmitting data in an active mode in an optical signal through a free-space optical path of a communication link extending across a terrestrial free-space region;

means for detecting degradation of the optical signal in the terrestrial free-space region; and

means for automatically switching from the active mode to a standby mode upon optical beam degradation in the terrestrial free-space region, wherein the standby mode includes transmitting data in a radio frequency (RF) signal through a free-space RF path of the communication link;

wherein an RF transceiver for generating the RF signal is active during the active mode and transmitting control and status information.

9. (Canceled).

App. No.: 10/840,172
Amendment

10. (Original): An apparatus in accordance with claim 8, wherein the means for detecting degradation of the optical signal in the terrestrial free-space region comprises:

means for sensing a characteristic of a received optical signal.

11. (Original): An apparatus in accordance with claim 10, wherein the characteristic of the received optical signal comprises a power level of the received optical signal.

12. (Original): An apparatus in accordance with claim 10, wherein the characteristic of the received optical signal comprises a transmissive capability of the received optical signal.

13. (Original): An apparatus in accordance with claim 10, further comprising:

means for using the characteristic of the received optical signal to calculate a power adjustment for a station at an opposite end of the communication link.

14. (Original): An apparatus in accordance with claim 8, wherein the degradation of the optical signal is due to atmospheric conditions in the terrestrial free-space region.

15. (Currently amended): A method for use in communications, comprising the steps of:

transmitting data in an optical signal through a free-space optical path of a communication link extending through a terrestrial free-space region;

detecting degradation of the optical signal; and

transmitting data through a backup communication path in

App. No.: 10/840,172
Amendment

response to detected degradation of the optical signal;
wherein the backup communication path is active and
transmitting control and status information while data is
being transmitted in the optical signal.

16. (Canceled).

17. (Currently amended): A method in accordance with
claim 15[[16]], further comprising the step of:
using the control and status information for switching
data transmission from the free-space optical path to the
backup communication path.

18. (Currently amended): A method in accordance with
claim 15[[16]], wherein content of the control and status
information is set according to a communication protocol.

19. (Original): A method in accordance with claim 15,
wherein the step of transmitting data through a backup
communication path comprises the step of:
transmitting data in a radio frequency (RF) signal
through an RF path of the communication link.

20. (Original): A method in accordance with claim 15,
further comprising the step of:
updating a control packet based on an assessed
characteristic of a received optical signal.

21. (Original): A method in accordance with claim 15,
further comprising the step of:
determining whether or not there is detected degradation
of the optical signal based on a control packet that is

App. No.: 10/840,172
Amendment

updated based on an assessed characteristic of a received optical signal.

22. (Original): A method in accordance with claim 15, wherein the step of detecting degradation of the optical signal comprises the step of:

sensing a characteristic of a received optical signal.

23. (Original): A method in accordance with claim 22, further comprising the step of:

using the characteristic of the received optical signal to calculate a power adjustment for a station at an opposite end of the communication link.

24. (Original): A method in accordance with claim 15, wherein the free-space optical path is subjected to atmospheric conditions.

25. (Currently amended): An apparatus for use in communications, comprising:

means for transmitting data in an optical signal through a free-space optical path of a communication link extending through a terrestrial free-space region;

means for detecting degradation of the optical signal;
and

means for transmitting data through a backup communication path in response to detected degradation of the optical signal;

wherein the backup communication path is active and transmitting control and status information while data is being transmitted in the optical signal.

App. No.: 10/840,172
Amendment

26. (Canceled).

27. (Currently amended): An apparatus in accordance with claim 25[[26]], further comprising:

means for using the control and status information for switching data transmission from the free-space optical path to the backup communication path.

28. (Currently amended): An apparatus in accordance with claim 25[[26]], wherein content of the control and status information is set according to a communication protocol.

29. (Original): An apparatus in accordance with claim 25, wherein the means for transmitting data through a backup communication path comprises:

means for transmitting data in a radio frequency (RF) signal through an RF path of the communication link.

30. (Original): An apparatus in accordance with claim 25, further comprising:

means for updating a control packet based on an assessed characteristic of a received optical signal.

31. (Original): An apparatus in accordance with claim 25, further comprising:

means for determining whether or not there is detected degradation of the optical signal based on a control packet that is updated based on an assessed characteristic of a received optical signal.

32. (Original): An apparatus in accordance with claim 25, wherein the means for detecting degradation of the optical

App. No.: 10/840,172
Amendment

signal comprises:

means for sensing a characteristic of a received optical signal.

33. (Original): An apparatus in accordance with claim 32, further comprising:

means for using the characteristic of the received optical signal to calculate a power adjustment for a station at an opposite end of the communication link.

34. (Original): An apparatus in accordance with claim 25, wherein the free-space optical path is subjected to atmospheric conditions.

35. (Currently amended): An apparatus for use in communications, comprising:

an optical transceiver configured to transmit data in an optical signal through a free-space optical path of a communication link extending through a terrestrial free-space region;

the optical transceiver further configured to detect degradation of a received optical signal; and

interface circuitry coupled to the optical transceiver that is configured to send data through a backup communication path in response to detected degradation of the received optical signal;

wherein the backup communication path is active and transmitting control and status information while data is being transmitted in the optical signal.

36. (Original): An apparatus in accordance with claim 35, wherein the backup communication path comprises a radio

App. No.: 10/840,172
Amendment

frequency (RF) path.

37. (Original): An apparatus in accordance with claim 35, wherein the optical transceiver is further configured to update a control packet based on an assessed characteristic of the received optical signal.

38. (Original): An apparatus in accordance with claim 35, wherein the interface circuitry is further configured to determine whether or not there is detected degradation of the received optical signal based on a control packet updated by the optical transceiver.

39. (Original): An apparatus in accordance with claim 35, wherein the optical transceiver is further configured to use an assessed characteristic of the received optical signal to calculate a power adjustment for a station at an opposite end of the communication link.

40. (Original): An apparatus in accordance with claim 35, wherein the optical transceiver is further configured to transmit data in the optical signal through a free-space optical path of the communication link that is subjected to atmospheric conditions.

41. (Currently amended): An apparatus for use in communications, comprising:

an optical transceiver configured to transmit data in an active mode in an optical signal through a free-space optical path of a communication link extending through a terrestrial free-space region;

the optical transceiver further configured to detect

App. No.: 10/840,172
Amendment

degradation of a received optical signal; and

interface circuitry coupled to the optical transceiver that is configured to automatically switch from the active mode to a standby mode in response to detected degradation of the received optical signal;

wherein the standby mode includes transmitting data in a radio frequency (RF) signal through a free-space RF path of the communication link;

wherein an RF transceiver for generating the RF signal is active during the active mode and transmitting control and status information.

42. (Original): An apparatus in accordance with claim 41, wherein the optical transceiver is further configured to update a control packet based on an assessed characteristic of the received optical signal.

43. (Original): An apparatus in accordance with claim 41, wherein the interface circuitry is further configured to determine whether or not there is detected degradation of the received optical signal based on a control packet updated by the optical transceiver.

44. (Original): An apparatus in accordance with claim 41, wherein the optical transceiver is further configured to use an assessed characteristic of the received optical signal to calculate a power adjustment for a station at an opposite end of the communication link.

45. (Original): An apparatus in accordance with claim 41, wherein the optical transceiver is further configured to transmit data in the optical signal through a free-space

App. No.: 10/840,172
Amendment

optical path of the communication link that is subjected to
atmospheric conditions.